

Specialty Bearings

Needle	Static	Weight	Dimensions	Typical	Known
Bearing	Capacity	(Grams)	IDxODxWidth	Application	Usage
BA 85 Z	600	4.4	1/2"x11/16"x 5/16'	Pivot	Yeti
B 812 OH	600	12.6	1/2"x11/16"x 3/4"	Pivot	Turner
HK 1010	950	3.3	10 x 14 x 10	Pedal	Speedplay
HK 1012	950	4.0	10 x 14 x 12		
HK 1012 1RS	950	4.0	10 x 14 x 12		
HK 1014 2RS	950	4.9	10 x 14 x 14	Pivot	Cannondale Pivot
HK 1210	1125	4.1	12 x 16 x 10	Pivot, Pedal	
HK 1210 1RS	1125	4.2	12 x 16 x 10	Pivot	
HK 1216 2RS	1535	11.8	12 x 18 x 16	Pivot	
HK 1416 2RS	1620	37.3	14 x 20 x 16	Pivot	
HK 1614 RS	1710	12.0	16 x 22 x 14	Pivot	Rocky Mountain
HK 1712	1850	11.7	17 x 23 x 12	Pivot	

Rod End	Weight	Dimensions	Typical	Known
Bearing	(Grams)	ID x thread	Application	Usage
Gar 6 UK	15.1	6mm x 1	Disc Brake Linkage	
Gar 8 UK	28.8	8mm x 1.24	Disc Brake Linkage	
POSB 4	17.6	1/4"x1/4" x 28tpi	Disc Brake Linkage	Foes
POSB 6	50.4	3/8"x3/8" x 24tpi	Disc Brake Linkage	

Sherical Plane	Weight	Dimensions	Typical	Known
Bushing	(Grams)	IDxODxWidth	Application	Usage
GE 6 EC	17.1	.375" X .812" .405'	Shock Mount	Foes
GE 12 EC	21.1	.5" X .875"X.437"	Shock Mount	
GE 6 UK	4.0	6 x 14 x 6	Shock Mount	
GE 8 UK	27.5	8 x 16 x 8	Shock Mount	
GE 10 UK	10.6	10 x 19 x 9	Shock Mount	
GE 15 UK	26.0	15 x 26 x 12	Shock Mount	